



NOSKOV, A.D., assistent State of phosphorus-calcium metabolism in the initial form of parodontosis. Stomatologiia 41 no.4:15-16 Jl-Ag '62. (MIRA 15:9) 1. Is kafedry terapevticheskoy stomatologii (zav. - prof. S.I. Vays) Irkutakogo meditsinskogo instituta. (GUNS--DISEASES) (CALCIUM METABOLISM) (PHOSPHORUS METABOLISM)







	Methodology for determining the economic efficiency of mechanization and automation in machinery manufacturing. Nauch.trudy MIEI no.18:173-176 *61. (MIRA 15:2) (Machinery industry) (Automation)						
	\$	•		·			
				•			
					and the second seco		
				• ·			
•				1		•	
				•.	,		
						•	
					•		




HE CONTROLLED BY THE PROPERTY OF THE PROPERTY


NOSKOV, A.I.

Stregthening machine-tool beds and reconditioning worn-out parts with T15E6 hard alloy. Mashinostroitel' no.1:16-17 Ja '63.

(MIRA 16:2)

(Machine tools-Maintenance and repair)





MOSKOV, A.I., inch.; PLETHEV, G.P., kand. tekhn. nauk; SKREBUSHEVSKIY, B.S., inch.

Study of a block consisting of a TP-80 boiler and VPT-50 turbine in sharply varying mode of operation. Izv. vys. ucheb. zav.; energ. 7 no.8:53-57 Ag *64. (MIRA 17:12)

1. Moskovskiy ordena Lenina energeticheskiy institut.

NOSKOV, A.I., inzh.; ROTACH, V.Ya., kand. tekhn. nauk, dotsent

Determination of the transfer function of a controlled object taking into account its time characteristic. Izv. vys. ucheb. zav.; energ. 8 no.1:75-82 Ja 165.

(MIRA 18:2)

1. Moskovskiy ordena Lenina energeticheskiy institut.

THE PROPERTY OF THE STATE OF TH


NOSKOV, A.I., kand. ekon. nauk

Evaluation and analysis of the economic efficiency of overall automation of production processes. Wekh. i avtom. proizv. 19 no. 10:31-35 0 165. (MIRA 18:12)

NOSKOV, A.I., inzh.; ROTACH, V.Ya., dotsent

Approximation of the time characteristic of an object using an aperiodic first-order link with delay. Izv. vys. ucheb. zav.; energ. 7 no.7299-102 J1 '64 (MIRA 17:8)

1. Moskovskiy ordena Lenina energeticheskiy institut. Predstavlena podsektsiyey avtomatizatsii teplovykh protsessov. Nauchno-tekhnicheskogo Soveta.



NOSKOV, A. I.

USSR/Kedicine - Typhangitie Kedicine - Epizcotic Diseases tug 1947

"Culticated Hushroom: Histoplasma Farciminosum as Propagators of Episcotic Lymphengitis," V. P. Koroleva, Chief Research Callaborator, A. I. Koskov, undidate in Veterinary V. P. Koroleva, Chief Research Callaborator, A. I. Koskov, undidate in Veterinary Sciences, N. V. Sychkov, Veterinarian, KH. A. Kahilovyan, Senior Research Collaborator, Scientific Research Laboratory for the Study of Toxic Mushrooms, 2 pp

"Veterim riye" Ro 8

Intracutaneous and subcutaneous ineculations of distorlesson fereimonosum culture into horses gave a tupical clinical aspect of the propagation of various types of episcotic lymphangitie. The incubation period was exactly two neather. The most effective method for contamination was by rubbing sushroom culture into scarified skim. Blastospores (cryptococcus) appear in the organs of the horse much scome than the first elinical symmetres of the disease. The transformation of the mycelium stage of the muchroom into the blastospore stage occurs within a period of 20 days after subcutaneous ineculation of the muchroom culture.

PA 36753 * Dzhilovyan. Rh. A

UBSR/Medicine - Epizontic Diseases Jun 4 Medicine - Bronchopneumonia, Therapy	
"Enzootic Bronchial Pneumonia in Young Pigs," A. I. Noskov, Cand Vet Sci, 2 pp	: ::
"Veterinariya" "No 6	
Discusses epizooticlogy, therapy, and prophylaxis of subject disease.	
31/497	70

NOSKOV, A. I.

"The influence of chemical and physical factors on certain toxic and pathogenic fungi."


Zhur. Mikrobiol., Epidemiol. i Immunobiol., No. 9, 1950, pp 30-35 in

Soviet

-W-24635 3 Dec 1952 p 7 (Microbiol. bibliography)

m

also MikrobioLogiya, voi 20, no 5, 1951



NOSKOV A. I.	Miso U-4723, 30 Sept 1953	IC IESER/Medicine - Infectious Diseases (Veterinary) (Contd) blue and Dahlia wielet for local therapy and of domestic acriding derivs for gen therapy, and clarification of possibility of transmission by insects.	"Veterinariya" Vol XIVIII,/pp 58-60 "Nich in	USSR/Medicine Infectious Diseases Apr. 51
		Apr 51	skin in i	51

Moskov, A. I.

Aug 53

USSR/Medicine, Veterinary - Epizootic Lymphangitis

"Allergenic Method of Diagnosis of Epizootic Lymphangitis in Horses," A. I. Noskov, Cand Vet Sci; V. P. Koroleva, Cand Biol Sci; All-Union Sci Hes Lab (VNIL) for the Study of Poisonous Fungi, Min of Agr and Supplies USSR

Veterinariya, Vol 30, No 8, pp 10-14

distoplasmin has proven to be a specific allergen; it is effective, as well as harmless; in the diagnosis of epizootic lymphangitis of horses caused by the yeast like fungus Histoplasma farciminosum (Cryptococcus farciminosus). Histoplasmin has been recommended by the Main Admin of Animal Husbandry of the Min of Agr and Supplies of the USSR. Histoplasmin is now generally available to specialists in veterinary medical practice

265 T 33

GREZIN, F.V., kandidat veterinarnykh nauk.; MOSKOV, A.I., kandidat veterinarnykh nauk.

THE REPORT OF THE PROPERTY OF


Use of antibiotics in gastrointestival diseases in young pigs and dysentery in hogs. Dokl. Akad. sel'khos. 21 no.9:3-6 %6.
(MERA 9:10)

1. Vsesoyusnyy nauchno-issledovatel'skiy institut veterinarnoy sanitarii i ektoparasitologii.
(Swine--Diseases) (Antibiotics)

SOSEDOV, P.O., direktor sovkhoza; KURTAVTSEV, P.F., starshiy veterinarnyy vrach; MOSKOV, A.I., kandidat veterinarnykh nauk.

Use ef antibiotics. Veterinariia 33 ne.8:78-79 Ag *56. (MLRA 9:9)


1.Sevkhoz *Petrevskeye*, Ukhtomskege rayena, Moskovskey oblasti. (Swina-Diseases and pests) (Antibiotics)



NOSEOV, A.I., kand. vet. nauk.

Use of a disinfection machine for treating the fleece of lambs in eases of trichophytia, Veterinariia 35 no.6155-56 Je '58.

(Ningvorm) (Lambs—Diseases and pasts) (NIRA 11:6)



NOSKOV, Arseniy Ivanovich, kand. veter.nauk; RYABOVA, Galina Semenovna, kand.veter.nauk; SOKOLOVA, G.S., red.; SAYTANIDI, L.D., tekhn. red.

[Control of ringworm in farm animals] Bortha so strigushchim lishaem seltskokhoziaistvennykh zhivotnykh. Moskva. Izd-vo M-va seltskoz.RSFSR, 1961. 58 p. (MIRA 15:7) (Cattle—Diseases and pests) (Ringworm)

NOSKOV, A. I. (Reviewer)

"Therapy and prophylaxis of ringworm infestation in agricultural animals." Veterinariya, Vol. 38, No. 3, 1961, p. 47.

general il externit en la company de la comp

NOSKOV, A. I., (Candidate of Veterinary Sciences, All-Union Scientific Research Institute of Veterinary Sanitation).

"Testing of the fungicidal properties of benzene hexachloride and DDT.

Veterinariya vol. 38., no. 11., November 1961., p. 72

NOSKOV, A.I., kand. veter. rauk; OCHKINA, I.I., kand. veter. nauk; VISHNYAKOVA, N.N., uchennyy zootekhnik


Hygenic characteristics of silage. Veterinariia 41 no.1:95-97 Ja '64. (MIRA 17:3)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut veterinarnoy sanitarii.

AKHMEDOV, A.M., prof.; DUSTOVA, R.T., aspirant; BELOV, Ye.M., kand.
veterin. nauk; ANTOKOVA, M.Ye., kand. veterin. nauk; HOSKOV, A.I.,
kand. veterin. nauk; LIPINA, A.N., aspirant; SIMONOV, A.P., aspirant;
BOCHAROV, D.A., kand. sel'skokhoz. nauk; KHRENOV, N.M., assistant

Sanitary and veterinary hygiene. Veterinariia 41 no.4:89-100 Ap '64. (MIRA 17:8)

1. Samarkandskiy sel'skokhozyaystvennyy institut (for Akimedov, Dustova). 2. Nauchno-proizvodstvennaya laboratoriya po bor'be s boleznyami molodnyaka sel'skokhozyaystvennykh zhivotaykh Ministerstva proizvodstva i zagotovok sel'skokhozyaystvennykh produktov RSFSR. (for Antonova). 3. Vsesoyuznyy nauchno- issledo-vatel'skiy institut veterinarnoy sanitarii (for Noskov). 4. Institut zhivotnovodstva Ministerstva sel'skogo khozyaystva Uzbekskoy SSR (for Lipina). 5. Vsesoyuznyy institut gel'mintologii imeni akademika K.I. Skryabina (for Simonov). 6. Moskovskiy tekhnologicheskiy institut myasnoy i molochnoy promyshlennosti (for Bocharov). 7. Khersonskiy sel'skokhozyaystvennyy institut imeni A.D. Tsyurupy (for Khrenov).



NOSKOV, A.I., kend. veterin. nauk

Testing the fungicidal effect of hexachloran and DDT. Veterinariia 38 no.11:72 N '61 (MIRA 18:1)

1. Vsesoyuznyy nauchnc-issledovatel'skiy institut veterinarnoy sanitarii.

NOSKOV, A.I., kand. veterin. nauk; SHARAPOV, V.M., mladshiy nauchnyy sotrudnik


Toxicity of mixed feeds infected with fungi. Veterinariia 41 no.1:84-85 Ja 165. (MIRA 18:2)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut veterinarnoy sanitarii (for Noskov). 2. Biologicheskiy institut Sibirskogo otdeleniya AN SSSR (for Sharapov).

McSKOV, A.I., kand.veterin.nauk; KOLESNIKOVA, Ye.A., veterinarnyy vruch

Measures for the control of ringworm. Veterinariia 41 no.3:35-37
Mr *65.

(MIRA 18:4)



ROGOVER, Grigoriy Borisovich. Prinimal uchastiya MOSEOF. A.M. astronomgeoderist. SMIRHOV, V.I., red.; FEDOROVA, L.M., red.izd-ve; BYKOVA, V.V., tekhn.red.

> [Characteristics of the Moril'sk deposit 1, having possible prospecting eignificance and the efficient method of prospecting it] Mestorozhdenie Moril'sk I, nekotorye ego osobennosti, mogushchie imet poiskovoe znachenie, i ratsional naia retodika ego razvedki. Moskva. Gos.nauchno-tekhn.izd-vo lit-ry po geologii i (MIRA 13:5) okhrane nedr. 1959. 167 p. (Woril'sk region-Ore deposits)

2308.2808.1413 18 1114

5/126/60/010/006/017/022 E111/E452

AUTHORS:

Guterman, S.G., Gol'dshteyn, M.I. and Noskov, A.Me.

TITLE:

Dispersion Hardening and Fine Crystal Structure of

Carbon Steel With Small Additions of Vanadium PERIODICAL: Fizika metallov i metallovedeniye, 1960, Vol.10, No.6,

pp.903-906

The object of the present work was to study the influence of small (0.01 to 0.093%) vanadium additions on the hardening of carbon steel and elucidate the causes of such hardening. Published investigations on this subject (Ref. 2 to 4) deal with relatively high vanadium contents. Induction melted type 40 steel 0.04% Aluminium was added in the furnace to deoxidize vanadium additions were made in the ladle or furnace. was used. Ingots were forged into 14 x 14 mm bars which were normalized from Fig.1 shows hardness as a function of tempering temperature (400 to 650°C for 1 hour) for hardened specimens with various vanadium contents: vanadium has no effect at 400°C but at higher temperatures it increases hardness. decreased if hardening temperature is reduced from 950 to 840°C.

Card 1/3

Card 2/3

S/126/60/010/006/017/022 E111/E452

Dispersion Hardening and Fine Crystal Structure of Carbon Steel With Small Additions of Vanadium

As shown in Fig. 2, the presence of 0.01% of vanadium increases the strength characteristics of hardened and tempered (600°C) specimens, further increases in vanadium having little effect; vanadium reduces plasticity somewhat. Chemical analysis of electrolytically produced carbide residues and mosaic block size determinations were carried out. For the latter, a type YPC-50M (URS-50I) X-ray ionization installation was used. shows, as functions of total vanadium content, the vanadium content in the carbide residues (as % of dissolved metal) and the hardness and block size for specimens hardened from 950°C and tempered at This shows that the hardening with small vanadium additions is due to precipitation of vanadium carbides and reduction in block size. This was confirmed by results (Fig. 4) for specimens of a heat with up to 1.7% V hardened from a temperature giving complete solution of carbides and tempered at 600°C. [Abstractor's note: The abscissa of Fig.2 and 4 There are 4 figures, 2 tables incorrectly designated as "W".]

5/126/60/010/006/017/022 E111/E452

Dispersion Hardening and Fine Crystal Structure of Carbon Steel With Small Additions of Vanadium

and 6 references: 4 Soviet and 2 non-Soviet.

ASSOCIATION: Ural'skiy nauchno-issledovatel'skiy institut chernykh metallov (Ural Scientific Research

Institute for Ferrous Metals)

hay 20, 1960 SUBMITTED:

Card 3/3

Determination of flave in small spheres. Zav.lab. 26 no.5:624-HOSKOV. A.M. 625 160. 1. Ural'skiy nauchno-issledovatel'skiy institut chernykh (Metals--Testing) (I rays-Equipment and supplies) metallov.

NOSKOV, A.S.

137-58-5-9096

Translation from: Referativnyy zhurnal, Metallurgiya, 1958, Nr 5, p 50 (USSR)

AUTHOR:

Noskov, A.S.

TITLE:

On a Project for a Compound Installation for the Recovery of Heat from Cooling Processes and From Waste Gases of an Openhearth Furnace (O proyekte kompleksnoy ustanovki po ispol'zovaniyu tepla okhlazhdeniya i tepla ukhodyashchikh gazov mar-

tenovskoy pechi)

PERIODICAL:

Tr. Nauchno-tekhn. soveshchaniya po ispol'zovaniyu vtorichnykh energ, resursov. Moscow-Leningrad, Gosenergoizdat

1957, pp 101-110

ABSTRACT:

The author describes the engineering project of a compound system for recovery of heat from cooling processes and from waste gases of an open-hearth furnace; the project includes provisions for generation of steam at an absolute pressure of 17 atm and a superheating temperature of 320°C. This is accomplished by means of combining equipment for evaporation cooling with heat recovery boilers and by employing the principle of forced circulation for this combination system. Caissons, internally lined, are of tubular design with welded collectors and

Card 1/2

137-58-5-9096

On a Project for a Compound (cont.)

with series-connected tubing. The pivot girders are made of steel and are drilled, as are the frames which are welded together from separate components. The cost of one ton of steam is expected to be 6.24-8.19 rubles; the initial construction expenses should be recovered within 1.26 years.

Ye.N.

1. Open hearth furnaces--Operation 2. Waste gases--Applications

Card 2/2

NOSKOV, A.S.

TUROVISEVA, Z.M.; LITVIHOVA, N.F.; MIKHATLOVA, G.V.; MOSKOV, A.S.; KEALITOV, R.Sh.

Apparatus for determining the content of gases in metals (with sureary in English). Zhur.anal.khim. 12 no.2:208-213 Kr-Ap '57. (KLRA 10:7)


1. Institut geokhinii i analiticheskoy khimii in. V.I. Vernadskogo skadenii nauk SSSR, Hostva.


(Chemical apparatus) (Gases in metals)


Noskov, A. S.
Noskov, A. S.

"Ryadushka" of the Rybinsk reservoir." Hoscow Technical Inst of the Fish Industry and Economy imeni A. I. Mikoyan. Moscow, 1956 (Dissertation for the degree of Candidate in Biological Science)

Knizhnaya letopis!







NOSKOV, B.A.; VASHCHNKO, K.I., professor, doktor tekhnicheskikh nauk.

redaktor; RUDENSKIT, Ya.V., tekhnicheskiy redaktor

[Manufacture of cast drop-forging dies] Profevodetvo lityth
moletovyth shtampov. Riev, Gos. nauchno-tekhn. isd-vo mashinostroit. lit-ry. 1953. 97 p. [Microfilm] (MLRA 7:10)

(Steel castings)

(Dies (Metalworking))

SUKHODOL'SKAYA. Te.A., kandidat tekhnicheskikh nauk; UL'YANOY, V.A., kandidat tekhnicheskikh nauk, retsensent; MOSKOV, B.A., kandidat tekhnicheskikh nauk, redaktor; HUDENSKIT, Ya., redaktor

[Materials for piston rings] Materialy porchaevyth kolets. Kiev. Gos, nauchno-tekhn, fed-vo mashinestroft, i sudestroft, lit-ry, (MIRA 7:8) 1953. 127 p. (Cast from) (Piston rings)

NOSKOV, B. A., jt. au.

The technology of casted parts. Izd. 2., perer. i dop. Moskva, Gos. nauchnotekhn. izd-vo mashinostroit. lit-ry, 1954. 278,2 p. (55-38811)

TS230.K63 1954

HOVIE. A.A., kandidat tekhnicheskikh nauk; HOSKOY, B.A., kandidat tekhnicheskikh nauk; HOSKOY, HOSKOY,

[The central factory laboratory] TSentral nais savodskais laboratoriis. [Khar'kov] Khar'kovskos obl. izd-vo, 1956. 82 p. (MERA 10:1)

1. Manastitel' machal'nika tsentral'noy zavodskoy laboratorii Khar'kovakogo zavoda transportnogo mashinostroeniya. (for Movik) (Engineering laboratories)

· Noskov, Boris ALEKSEY EVICH

PHASE I BOOK EXPLOITATION

399

Noskov, Boris Alekseyevich, and Smelyakov, Nikolay Nikolayevich

Konstruirovaniye litykh detaley (Design of Cast Parts) Kiyev, Mashgiz, 1957. 210 p. (Biblioteka konstruktora) 8,600 copies printed.

Sponsoring Agency: Nauchno-tekhnicheskoye obshchestvo mashinostroitel'noy promyshlennosti. Kiyevskaya oblastnaya organizatsiya.

Reviewer: Ryzhikov, A. A., Doctor of Technical Sciences, Professor; Ed.: Soroka, M. S.; Tech. Ed.: Rudenskiy, Ya. V.

PURPOSE: This book is designed as a manual for engineers, designers and technicians engaged in machine building. It may also be used by foundry engineers.

COVERAGE: The authors stress the importance of castings in machine design. In this book they describe the elements of design of ferrous and nonferrous castings. A few chapters are devoted to various methods of casting such as investment precision casting, pressure casting, centrifugal casting,

is and all all actions are the second and the second actions and the second actions are second as the second actions are second as the second actions are second as the second action ac

Card 1/5

Design of Cast Parts 3	99
the use of permanent and shell molds, and the applicating to cast iron elements.	lication of
TABLE OF CONTENTS: Introduction	3
Ch. I. General Characteristics of Casting Alloys	4
Flowability Shrinkage Warping Crystallization of alloys Liquation	4 11 14 25 34
Ch. II. Mechanical and Special Properties of Metals an Selection of Metals for Cast Parts	d · 35
Ch. III. Requirements for Designing Castings as Determ by Considerations of Mold Manufacture	ined 80
Card 2/5	

399	
gn of Cast Parts	80
Design of the Outer Contours of Castings	83 85 89 90 92 94 101
hesigh or posses and provide	89
	90
he cornining tion of past and	92
Mmensioning of themand acquired of dastings	94 101
Dimensioning of Drawings Tolerances and dimensional accuracy of castings Toner Contours of castings (use of cores) Inner Contours of castings	108
Allowances for machining	111
Standardisation	
nestering Cost Farts	112
IV. General Rules for Designing Cast Farts	114
V. Design of castings	** **
A. Marking or company	121
VI. Design of Gray Cast Iron Castings	
. VII. Design of Castings of Modified Cast Iron and Cas Iron Containing Spherical Graphite	130
rd 3/5	
rd 3/5	

esign of Cast Parts	399	
h. XVIII. Bimetal Castings	190	į
h. XIX. Considerations in Selecting Casting	Methods 191	
h. XX. Quality Control of Castings	196	
h. XXI. Defects and Correction of Defects in	Castings 201	
onclusion	204	
ibliography	205	
VAILABLE: Library of Congress		
)/vm -11-58	

HOSKOV, B.11.

137-58-3-5445

Translation from: Referativnyy zhurnal, Metallurgiya, 1958, Nr 3, p 136 (USSR)

AUTHOR: Noskov, B.A.

TITLE: Fabrication by Means of Welded Castings (Svarnolityye detali)

PERIODICAL: Tr. Khar'kovsk. politekhn. in-ta, 1957, Vol 11, pp 25-37

ABSTRACT: Technological, production-cost, and organizational problems connected with the substitution of castings by welded castings

were examined on the following examples: a) a gas compressor housing weighing approximately 45 tons; b) a turbine runner 4165 mm in diameter consisting of two cast disks and blades of rolled metal; c) the front support for the boiler of a locomotive; d) guiding trough of a stripping crane; e) the tripod for the reeling unit of a wire drawing mill; f) a king-bolt support for a railway car; g) a steam superheater box. The author lists a number of cast components which, at the present time, can not

be replaced by welded castings.

Bibliography: 10 references. V.S.

Card 1/1

Woskov, B.A.

AUTHOR: Ginzburg, Z.L., Engineer,

128-58-4-15/18

TITLE:

Scientific-Technical Session on Progressive Technology of Casting Wolds (Nauchno-tekhnicheskaya sessiya po progressiv-

noy tekhnologii liteynoy formy)

PERIODICAL:

Liteynoye Proizvodstvo, 1958, No. 4, pp 28-30 (USSR)

ABSTRACT:

A conference on the technology of casting molds - organized by the NTOMAShPROM of the Khar'kov Oblast' - convened in Khar'kov on 14-16 November 1957. More than 200 delegates from plants, research institutes, vuzes and other organizations of the Khar'kov and other regions participated. Problems of earth-mold casting were discussed. A total of 24 reports were delivered on hardening and exothermic mixes and the mechanized processes in USSR and abroad. B.A. Noskov and V.I. Ryzhkov (KhPI) gave information on molding sand and clay available in the Khar'kov economic region. The following reports were also heard: V.V.Ryabova - on the use of carbon dioxide, at NKMZ, for chemical strengthening of molds, which has reduced the drying period and cut the consumption of generator gas, improved the quality of castings, and nearly

Card 1/5

Scientific-Technical Session on Progressive Technology of Casting Folds

doubled the production of molds; R.Kh. Ivanov - on the use of the same quick-hardening mixes, with cold carbon dioxide, at the Slavyanskiy mashinostroitel'nyy zavod (Slavyansk Lachinebuilding Plant); Engineer D.A. Lur'ye (Giprostanok) - on modern methods and an installation for production of carbon dioxide; Engineer Ye.P. Tolmachev of the Voroshilovgradskiy teplovozostroitel nyy zavod (Voroshilovgrad Diesel-Locomotive Plant) on experience with molding sand milled in a special vibration mill, which solves the problem of obtaining castings with a clean surface not only with shell molds, but also with conventional molding methods; A.Ya. Izmalkov - on the oil-less binder "P" used at the plant "Serp i Molot"; A.I. Veynik - on the theory of forced cooling of castings and the experience in this method at the Novo-Kramatorskiy i kinskiy stankostroitel'nyy zavodov (Novo-Kramatorsk and Minsk Machine Tool Plants) which developed this method in the production of large castings; I.V. Ryzhov - on the physico-chemical nature of sand crust (on castings) and the ways of eliminating this crust by producing a de-oxidizing atmosphere between the mold and the metal, casting in vacuum, or crystallization-preventive additions to water glass; P.G. Novikov (of TsNIITMASh) - on

Card 2/5

sasan ningan kerantah di sebagai sebaga

128-58-4-15/18

Scientific-Technical Session on Progressive Technology of Casting Molds

results of the collective work of TsNIITMASh and NKMZ on technological problems of the production of large molds, and the new method of forced or controlled cooling of castings in the ground, as well as on the experiments with a system of universally applicable cast parts; B.K. Dymshin of the Khar!kovskiy turbinnyy zavod (Khar'kov Turbine Plant) and Engineer I.Ye. Gabey (NKMZ) - on exothermic mixes for heating the feeding heads of steel and cast iron castings; H.L. Turovskiy on investigation of internal stresses at the Khar'kovskiy zavod transportnogo mashinostroyeniya (Khar'kov Plant of Transport Kachines); V.S. Ladnov - on mechanized casting into shell molds by shot-strewing the mold boxes, being introduced at the same transport machine plant; K.I. Kostinenko - on the organization of boxless molding at the plant Rostsel mash; N.A. Gerasimov of the Kremenchugskiy zavod dorozhnykh mashin (Kremenchug Road Machine Plant) - on casting parts in molds produced under pressure up to 100 kg/cm2, without mold boxes, which nearly completely eliminates the necessity of machining the castings and greatly reduces the consumption of foundry materials and metal; A.M. Petrichenko of the Khar'kovskiy

Card 3/5

128-58-4-15/18

Scientific-Technical Session on Progressive Technology of Casting Holds

avtodorozhnyy institut (Khar'kov Auto-Road Institute) - on the experience of the Chinese Democratic Republic with semipermanent molds for thin-wall castings; Ye.A. Sukhodol'skaya of the Khar'kovskiy politekhnicheskiy institut (Khar'kov Polytechnical Institute) - on some peculiarities of foundry technology in China; V.D. Bezuglov of the Khar'kovskiy zavod zubovrachebnykh materialov (Khar'kov Plant of Dentistry Materials) - on self-hardening plastics "AST" which is readily machineable, well suited for decorative correction of surface faults on metal castings, and also for making light core boxes, press-molds for wax patterns, etc. The conference recommended that the Khar'kov Sovnarkhoz organize the exploitation of molding sands and clays in the region and a centralized production of carbon dioxide. The conference pointed out the necessity of extensive use of quick-drying mold mixes, forced cooling of castings, exothermic mixes for heating the feeding heads, and the necessity to introduce the shell-mold and the chill-casting methods. The method of making molds

Card 4/5

128-58-4-15/18


Scientific-Technical Session on Progressive Technology of Casting Molds

under high pressure was recommended for use. The importance of the Khar'kov Dentistry Exterials Plant and KhTZ work with self-hardening plastics for foundry use was emphasized.

AVAILABLE: Library of Congress

1. Castings-Scientific reports

Card 5/5



SOV/128-58-11-8/24

AUTHORS:

TITLE:

Noskov, B.A., Rozenberg, Yu.G., Tsukerman, S.I., Den'gin, I.N.

A STATE OF THE PARTY OF THE PAR

A Coke-Gas Cupola Furnace (Koksogazovaya wagranka)

PERIODICAL:

Liteynoye proizvodatvo, 1958, Nr 11, pp 14-15 (USSR)

ABSTRACT:

The use of natural gas in cupola smelting leads to reduced coke expenses. Experiments carried out at the Khar'kovskiy elektromekhanicheskiy zavod (Khar'kov Electromechanical Plant) proved that the successful use of gas and coke depends on proper gas burning conditions, i.e. on the design of burners and their position in the cupola. It was stated that good results can be obtained by placing the burners above the tuyeres. Further investigations will be concentrated on determining the optimum dimensions of the distance between the burner axes and the tayeres. The information includes a description of a cupola where normal conditions for gas burning and reduced coke expenses were obtained by reducing the number of tuyeres from 6 to 4. A new improved

card 1/2

A Coke-Gas Cupola Furnace

SOV/128-58-11-8-24


cupola design, now being installed, will make possible a further reduction in coke expense by a change in air distribution. There are 3 diagrams and 1 photo.

- 1. Blast furnaces—Equipment 2. Blast furnaces—Operation
- 3. Natural gas--Performance

Card 2/2

表现是1000年的1000年的1000年的1000年的1000年的1000年的1000年的1000年的1000年的1000年的1000年的1000年的1000年的

RYZHKOV, I.V.; NOSKOV, B.A. Hature of sand burning and measures for its prevention. Trudy
(MIRA 14:7) KhPI 21 Ser.met. no.4:37-49 159. (Founding)



TYUTYUNNIKOV, B.N., prof., doktor tekhn.nauk; NOSKOV, B.A., dotsent, kand. tekhn.nauk; RYZEKOV, I.V., kand.tekhn.nauk; PEPENKO, V.D., assistent; BOGDAN, I.V., inzh.

Liquid water glass mixtures. Izv.vys.ucheb.zav.; mashinostr. no.4: 60-63 '60. (MIRA 14:4)


1. Khar kovskiy politekhnicheskiy institut. (Soluble glass)

MOSKOV, B.A., kand.tekhm.nauk; MAKARENKO, S.F., insh.; SUMMSOV, V.F.,
insh.; STOTANGHENKO, S.I., insh.

Blowing gases through liquid metals. Mashinostroenie no.6:
79-43 M.D '62.

1.Khar'kovskiy politekhnicheskiy institut (for Noskov).
2. Luganskiy veohemiy mashinostroitel'nyy institut (for Makarenko, Sumtsov).
3. Luganskiy zavod im. Farkhomenko (for Stoyanchenko).

(Metallurgy)



DEN'GIN, I.N.; KASHIRSKIY, A.V.; NOSKOV, B.A.

Relation between hydrogen content in the furnace-top gas of a coke-and-gas cupola and in the pig iron being melted. Izv. vys. ucheb. zav.; chern. met. 6 no.6:168-171 '63. (MIRA 16:8)

1. Khar'kovskiy politekhnicheskiy institut.
(Cast iron—Hydrogen content) (Gases—Analysis)

NOSKOV, B.A., kand.tekhn.nauk; MAKARENKO, S.F., inzh.; SHUT'YEV, Yu.S., inzh.

Effect of the nitrogen blast on the structure and properties of cast iron. Mashinostroenie no.4:40-43 J1-Ag '63. (MIRA 17:2)

1. Khar'kovskiy politekhnicheskiy institut (for Noskov). 2. Luganskiy vecherniy mashinostroitel'nyy institut (for Makarenko, Shut'yev).

NOSKOV, Boris Alekseyevich, kand. tekhn. nauk; DEN'GIN, Igor'
Nikolayevich, kand. tekhn. nauk; TARASENKO, V.S., inzh.,
retsenzent

[Using natural gas for the melting of cast iron] Primenenie prirodnogo gaza pri vtorichnoi plavke chuguna. Kiev, Tekhnika, 1964. 114 p. (MIRA 17:8)


BOBKO, Yuriy Georgiyevich, NOSKOV, B.A., prof., retsenzent; LYUBCHENKO, A.P., kand. tekhn. nauk, retsenzent; SAKHAROVA, A.V., dots., otv. red.; KOVALEVA, Z.G., red.

[Aluminum cast iron] Aliuminievye chuguny. Khar'kov, Izd-vo Khar'kovskogo univ., 1964. 194 p. (MIRA 17:6)

CENTEST REST HARM HARM REPORTED BY THE STATE OF THE STATE

NOSKOV, B.A.; TSUKFRMAN, S.I.

Matallurgical characteristics of remelting cast iron acrap.
Lit. proisv. no.2:3-5 F 165. (MIRA 18:6)



NOSKOV, B.A., doktor tekhn. nauk

Gas-fired iron-melting furnace. Lit. proizv. no.1:13-14 Ja '66.

(MIRA 19:1)

ARTHIPOV, P.P., inghener; IVANOV, Ye.D., inghener; XRYLOV, E.V., inghener-arkhitektor; MIKANDROV, B.I., inghener-arkhitektor; MOKKOY, B.G., inghener-arkhitektor; RYABTSEV, M.E., vetvrach; SOEHRABICHEV, R.E., inghener-arkhitektor; TEIBUL'SKIY, L.A., kandidat gel'skokhogyaystven-nykh nauk; PIOTROVSKIY, K.I., inghener, retgengent; VOL'ROVSKAYA, V.E., redaktor; FEDOTOVA, A.F., tekhnicheskiy redaktor.

[Handbook on the construction of farm buildings] Spravochnik po sel'sko-khoziaistvennomn stroitel'stvu. Moskva, Gos. izd-vo selkhoz. lit-ry.
Vol. 2. 1952. 579 p. (MERA 8:2)
(Farm buildings) (Building)

ARKHANGEL'SKII, P.Ye., inzhener; ARKHIPOV, P.P., inzhener; VAS'KOV, M.P., agronen; ZHRUDSKIY, D.A., arkhitektor; IVANOV, A.P., arkhitektor; KIBI-HAV, S.F., arkhitektor; KRYLOV, M.V., inzhener-arkhitektor; KULAKOV, D.V., arkhitektor; MARTYHOV, P.F., inzhener; HIKIFOROV, V.S., inzhener; MOSKOV B.G., arkhitekter; PETUKHOV, B.V., kandidat tekhnicheskikh nauk; RUDAHOF, M.L., kandidat tekhnicheskikh nauk; RYAZANOV, V.S., kandidat arkhitektury; SOKHRANICHEV, N.S., inzhener-arkhitektor; TARASOV, D.I., arkhitekter; SHMIDT, N.E., kandidat arkhitektury; KHOKUTOV, Ye.Ye., arkhitektor; VOL'FOVSKAYA, V.N., redaktor; FEDOTOVA, A. F., tekhnicheskiy redaktor.

[Handjock on the construction of farm buildings] Spravochnik po sel'skokhesimistvennemu stroitel'stvu. Avtorskii kollektiv: P.E.Arkhangel'skii
i dr., avtor-sost. N.V.Krylov. Koskva, Gos.izd-vo sel'khoz.lit-ry. Vol.3
1955 843 p. (Farm buildings) (KIRA 9:6)

HATSENTOV. D.I., kandidat sel'skokhozysystvennykh nauk; MERTCH'YAN, V.S., kandidat sel'skokhozysystvennykh nauk; ARKHANGZL'SKIY, P.Ye., inzhensr; MOSKOV, B.G., arkhitektor; KRASNOSHCHEKOV, H., redaktor; LIL'YE, A., tekhnicheskiy redaktor

[Greenhouses, hotbeds and heated soil] Teplitsy, parniki, uteplennyi grunt. [Hoskva] Hoskovskii rabochii, 1956. 246 p. (HIRA 9:9)

1. Hauchno-issledovatel'skiy institut ovoshchnogo khozyaystva (for Natsentov. Mkrtch'yan) 2. Respublikanskiy gosudarstvennyy institut proyektirovaniya sovkhoznykh predpiyatiy - Rosgiprosovkhozstroi) (for Arkhangel'skiy). 3. Vsesoyuznyy gosudarstvennyy institut proektirovaniya sel'skokhozyaystvennykh predpriyatiy - Soyuzgiprosel'khoz (for Noskov)

(Hotbeds) (Soil heating) (Greenhouses)


EREMER, G.I., doktor tekhn.nauk, prof.; GALDIN, M.V., inzh.; DEMIN, A.V., kand.tekhn.nauk; ZYABLOV, V.A., kand.tekhn.nauk; KAPLUNOV, M.M., inzh.; KASHKOV, L.Ya., inzh.; KOROLEV, V.F., kand.tekhn.nauk; KRASHOV, V.S.; KULIK, M.Ye., kand.tekhn.nauk; MAKAROV, A.P., inzh.; HOVIKOV, G.I., kand.tekhn.nauk; HOSKOV, B.G., inzh.; OLENEV, V.A., kand.vet.nauk; OSTANKOV, V.P., inzh.; PERCHIKHIN, A.V., inzh.; POKHVALENSKIY, V.P., kand.tekhn.nauk; SERAFIMOVICH, L.P., kand.tekhn.nauk; SMIRNOV, V.I., kand.tekhn.nauk; URVACHEV, P.N., kand.tekhn.nauk; FADEYEV, N.H., inzh.; FATEYEV, Ye.M.; KRYUKOV, V.L., red.; VESKOVA, Ye.I., tekhn.red.

图:100mm 100mm 100

[Reference book on the mechanization of stock farming] Sprayochnaia kniga po mekhanizatsii zhivotnovodstva. Moskva, Gos.izd-vo sel'khoz. lit-ry, 1957. 678 p. (MIRA 10:12)

1. Chlen-korrespondent Vsesoyuznoy akademii sel'skokhozyaystvennykin nauk im. V.I.Lenina (for Krasnov, Fateyer).

(Farm equipment) (Stock and stockbreeding)



Nostor, B.M.

USSR/Physics - Technical physics

Card 1/1 Pub. 22 - 16/40

Authors

Gruzin, P. L.; Noskov, B. M.; and Shirokov, V. I.

Title

: Effect of Mn on the self-diffusion of Fe

Periodical : Dok. AN SSSR 99/2, 247-250, Nov 11, 1954

Abstract

Fight Fe-Min alloys were investigated to determine the effect of Min on the selfdiffusion of the Fe in austenite. The thermal dependence of the self-diffusion coefficients of Fe in the gamma-phase of Fe-Min alloys was investigated by the method of radioactive indicators through the utilization of the artificiallyradioactive Fe59 isotope. The self-diffusion coefficients were calculated on the basis of data obtained by measuring the integral radioactivity of the sample. It was found that the bond between the atoms of the basic alloy during the addition of the second element increases. The energy of activation of Fe self-diffusion at an In content of 8% was established as greater than the activation energy of pure iron self-diffusion. Seven references; 6-USSR and 1-USA (1938-1954). Tables; graphs.

Institution:

Central Scientific Research Institute of Ferrous Metals, Institute of Metallurgy and Physics and State University, Institute of Chemistry, Gorkly

Presented by: Academician G. V. Kudryumov, June 5, 1954

GRUZIE, P.L., kand.fiz.-mat.nauk; NOSKOV, B.K., kand.fiz.-mat.nauk; SHIROKOV,
V.I., kand.fiz.-mat.nauk.

Effect of manganese on the self-diffusion of iron. Probl. metalloved.
i fiz. met. no.4:503-508 '55.

(Biffusion) (Iron) (Manganese)

"APPROVED FOR RELEASE: Tuesday, August 01, 2000

CIA-RDP86-00513R001137

NOSKOV, B. ITT.

Category: USSE/Solid State Physics - Diffusion. Sintering E-6

Abs Jour : Ref Zhur - Fizike, No 3, 1957, No 6681

Author : Noskov, B.M., Kuznetsov, Ye.V., Shcherbedinskiy, G.V.

Inst : Gor'kiy, USSR

Title : Influence of Intregrenular Separation Boundaries on the


Coefficient of Self-Diffusion of Iron in Iron-Nickel Gerbon

Alloys.

Orig Fub: Fiz. metallov, i metallovedeniye, 1955, 2, No 3, 489-493

Abstract: The coefficient of self-diffusion of iron is 2-3 times greater in alloy specimens that have been subjected to martensitic transformation and have been again restored to eustenite, then in specimens that have not been subjected to martensitic transformation. This is caused by the presence of traces of provious martensite boundaries, along which intercrystelline diffusion is more rapid. These traces are eliminated gradually as the temperature increases during the time of heating. The energy of activation of the process of eliminating the traces is nearly equal to the activation energy of the intercrystelline self-diffusion.

Cerd : 1/1



NOSKOV, B.M.; PAVLOV, P.V.; SHCHERBEDIUSKIY, G.V.

Diffusion of tin in d and f-phases of the system copper - tin.

Isv. vys. ucheb. sav.; fis. no.4:163-167 '59. (HIRA 13:3)

1.Fiziko-tekhnicheskiy institut Gor'kovskogo gosumiversiteta ineni

N.I. Lobachevskogo.

(Copper-tin alloys)

18.7500

67761

SOV/126-8-5-14/29

AUTHORS:

Zelinskiy, M.S., Noskov, B.M., Pavlov, P.V., and

Shitova, E.V.

TITLE:

Influence of Vanadium Additions on the Self-Diffusion

of Iron

PERIODICAL: Fizika metallov i metallovedeniye, 1959, Vol 8, Nr 5,

pp 725-730 (USSR)

ABSTRACT: In contrast to the effect of many other transition elements, vanadium has been found to give a weaker atomic bonding than occurs in pure iron (Refs 6, 7). Since for other metals results of diffusion and X-ray investigations agree, the authors decided to study the self-diffusion of iron with respect to vanadium content. Although this had already been studied, work by Sanadze and Tsivtsivadze (Ref 8) has thrown doubt on some previous results (Refs 4, 5, 9). The present authors used three Fe-V (0.48, 1.01 and 2.04% V) and two Fe-V-C (0.096, 2.46% V and 0.820, 0.25% C, respectively)

Card 1/3

alloys (compositions shown in Table 1). 5 x 8 x 25 mm plane parallel specimens were subjected to homogenizing annealing at 1100 °C for 20 hours. thickness of about 0.005 mm of radioactive Fe59 was electrodeposited on one face. Pairs of specimens with)

67761 SOV/126-8-5-14/29

Influence of Vanadium Additions on the Self-Diffusion of Iron their active faces in contact work subjected to

their active faces in contact were subjected to isothermal diffusion annealing for 4-200 hours in a quartz tube evacuated to 10-3 mm Hg. Temperature (900-1300 and 1100-1340 for the Fe-V and Fe-V-C alloys, respectively) was controlled to ± 5 °C. After annealing specimens were rapidly quenched and the self-diffusion coefficients determined by removing layers and measuring the integral residual gamma-activity of the remainder of the specimen (Ref 10), with precautions to avoid end effects. Two to four independent determinations were made at each temperature. break at 1100 °C on the curve of log D vs inverse of absolute temperature it was deduced that below this temperature inter-crystallite diffusion plays a big part. Results above 1100 °C referred to uniform diffusion and were used in calculating the coefficients: these and other diffusion parameters are shown in Table 2. Table 3 the corresponding data for inter-crystallite diffusion calculated by Fisher's formula (Ref 11) are given for the Fe-V alloys. The linear relation between the logarithm of the uniform diffusion coefficient and

Card 2/3

APPROVED FOR RELEASE: Tuesday, August 01, 2000 CIA-RDP86-00513R0011373

67761

SOV/126-8-5-14/29 Influence of Vanadium Additions on the Self-Diffusion of Iron

the activation energy for these alloys is shown in Fig 2; in Fig 3 the activation energy is shown as a function of the vanadium concentration, showing that the activation energy decreases linearly with increasing vanadium concentration. The authors discuss this and other properties of vanadium in relation to those of similar metals. There are 3 figures, 3 tables and 15 references, of which 13 are Soviet, 1 is English and 1 is French.

ASSOCIATION: Issledovatel skiy fiziko-tekhnicheskiy institut

g. Gor'kiy (Physico-Technical Research Institute, Gor'kiy) Card 3/3 SUBMITTED: May 29, 1959

ACCESSION NR: AR4022439

S/0058/64/000/001/A037/A037

SOURCE: RZh. Fizika, Abs. 1A339

AUTHOR: Kanter, B. Z.; Lermontov, V. V.; Noskov, D. A.; Yushkov, Yu. G.

7411中国11组88221度是基础设备的建筑是建筑在2000元的设备的发展,但是这位大型设备的发展。

TITLE: 5-MeV microtron

CITED SOURCE: Izv. Tomskogo politekhn. in-ta, v. 122, 1962, 45-49

TOPIC TAGS: microtron, microtron characteristics, microtron electromagnet, particle accelerator, accelerator, electron injection

TRANSLATION: The 5-MeV microtron of the Tomsk Polytechnic Institute is described (RZhFiz, 1963, 1A401--403). The high frequency section of the amplifier includes a magnetron oscillator, two phase shifters, an absorbing load, and a toroidal cavity with Q of approximately 2000. The electromagnet poles had a diameter of 55 cm and the mag-

Card 1/2

ACCESSION NR: AR4022439

netic core had a cross section 30 x 12 cm. All the main units of the accelerator were constructed in 1959. During the starting, problems involved in the optimal coupling between the resonator and the waveguide were investigated, along with the possibility of using an incandescent cathode for electron injection. The current attained to date on the ninth orbit (5 MeV energy) is several microamperes per pulse. K. Belovintsev.

DATE ACQ: 03Mar64

SUB CODE: PH, SD

ENCL: QO

Card 2/2

	L_181711-66ENT(m)/ENP(v)/T/ENP(t)/ENP(k)	•	
28 2	AUTHOR: Kaz'min, G. S.; Noskoy, D. A.; Pankovets, N. G.; Proskurovskiy, D. I.; Shangin, A.S.		
Se many of supplies of succession	ORG: none 44.55 TITIE: Electron-beam welding of materials in a vacuum		
	SOURCE: Ref. zh. Metallurgiya, Abs. 12E283		
	REF SOURCE: Sb. dokl. k Novosib. nauchno-tekhn. konferentsii po mashinostr. Ch. 1. Novosibirsk, 1964, 115-122		
	TOPIC TAGS: electron beam welding, vacuum welding, metal cutting THANSIATION: The authors december to		
	TRANSLATION: The authors describe the advantages of the electron-beam method for welding metal over other methods. Units are described for welding, drilling and cutting metals with the use of an electron beam. These installations were developed in the Department of Electronic Devices at the Tomsk Institute of Radicelectronics and Electronic Technology. V. Fomenko [JPRS]	1 1	
	SUB CODE: 13		1
22.0	UDC: 621.791.72	Z	

ACC NR. AR7002223 SOURCE CODE: UR/0275/65/000/010/V002/V002

AUTHOR: Noskoy, D. A.; Proskurovskiy, D. I.

TITLE: Using alternating voltage to feed an electron welding gun

SOURCE: Ref. sh. Elektronika i yeye primeneniye, Abs. 10V10

REF SOURCE: Tr. Tomskogo in-ta radioelektron. i elektron. tekhn. no. 4, 1965, 102-103

TOPIC TAGS: welding equipment, electron gun, welding electrode, religional form for the coloring coloring.

ABSTRACT: Experimental electron-beam welding equipment is described in which the electron gun is fed with alternating voltage. The unit uses the rectifier properties of the electron gun, which functions as a rectifier with high internal resistance. The parts intended for welding are heated only during the negative half-cycles. The anode of the electron gunis grounded, while the cathode is fed alternating voltage by a step-up transformer winding. In this connection, the use of a magnetic focus-

ing beam is impaired and electrostatic focusing may be used. However, it requires a proportional change of voltage in all the electrodes. The cathode and cathodic electrode are under the same potential with respect to the anode, simplifying the

Card 1/2

APPROVED FOR RELEASE: Tuesday, August 01, 2000 CIA-RDP86-00513R0011373

UDC: 621.38:62

ACC NR: AR7002223	
design and the circuit controlling the beam current. With this design, the election will produce a conic converging beam with a high current density. The resonant and welding conditions are presented. Orig. art. has: 1 figure a bibliography of 2 titles. [Translation of abstract]	tron ults and [NT]
SUB CODE: 15, 07/	
-d 2/2	

ACC NR AR7002221 (AN) SOURCE CODE: UR/0275/66/000/010/A011/A011 AUTHOR: Kaz'min, G. S.; Noskov, D. A.; Pankovets, N. G.; Sudakov, V. I.; Proskurovskiy, D. I. TITLE: Electron-beam welding of leads in electrovacuum devices SOURCE: Ref. zh. Elektronika i yeye primeneniye, Abs. 10A74 REF SOURCE: Fr. Tomskogo in-ta radioelektron. i elektron. tekhn., no. 4, 1965, 112-114 TOPIC TAGS: electron beam welding, tungsten making, nickel waking, flux, tensished mine electroracuum, electroracuum equip weld evaluation ABSTRACT: An experimental investigation was nade of electron-beam welding of leads in electrovacuum equipment, which were made of tungsten and nickel components. Acted upon by the accelerated and focused electron beam in vacuum, the tungsten component generates the heat which fuses the ends of the two wires. The leads are welded on an electron beam device. The components to be welded are fastened to a mandrel, placed in the operating chamber. During welding, the com-Card 1/2 HDC - 621 3 032

ACC NR. AR7002	221	
scopic analysis	ught to a distance at 0.2—0.3 mm. The nickel component is fed apponent by a spring mounted on the mandrel. An unetched micro-500X showed no defects in the weld. The weld was dense, without and inclusions. [Translation of abstract]	1
SUB CODE: 13		
•		
		_
2/2		

ACC NR: AR7002220

SOURCE CODE: UR/0275/66/000/010/A001/A001

AUTHOR: Noskov, D. A.; Ponomareva, L. P.; Sokolov, Yu. M.

这些种的**计算针用计算数据解析的数据相似,并不可能能够指示。他的**数据是比较多效的 R.O. 数异类和外壳的对象化类的物质的对象性的对象的现代生活,

TITLE: Testing of certain types of cathodes in near vacuum conditions

SOURCE: Ref. zh. Elektronika i yeye primeneniye, Abs. 10A2

REF SOURCE: Tr. Tomskogo in-ta radioelektron. i elektron. tekhn., no. 4, 1965, 90-94

TOPIC TAGS: cathode, tungsten cathode, betatron cathode, rhenium cathode, nickel cathode, lanthanum hexaboride cathode, ion bombardment, cathode emission

ABSTRACT: Three types of cathodes are analyzed: boride-lanthanite, oxide-thorium and a heater-baked cathode. Selection of the type is determined by its working conditions in a betatron injector. Requirements imposed on these cathodes are the following: high emission capacity; resistance to ion bombardment and contamination by residual gases; satisfactory operation under high voltage; mechanical strength and ease of operation; and long service life. Examination of

Card 1/3

UDC: 621.385.7

ericilistatismus in experience de la comparación de la comparación de la comparación de la comparación de la c

ACC NR: AR7002220

the influence of ion bombardment on lanthanite hexaboride cathodes has shown their stability to exceed considerably that of tungsten and rhenium. After the termination of the experiment, the boride-lanthanite cathode was kept in open air for 24 and 30 hours, after which its emission qualities were reexamined. The experiment showed that the cathodes fully recuperate their emission qualities and require no special activation. The strong heater current, which is the shortcoming of these cathodes, can be decreased by changing their dimensions or by indirect heating. The baked (impregnated) cathode, consisting of 70% nickel powder and 30% ternary carbonate, sintered with a nickel sublayer, is one of the cathodes most suitable for the betatron injector. Experiments show that the catnode completely recuperates its emission qualities after long exposure to the air and lengthy activation. Emission without additional activation decreases by a factor of two. Emission stability tests were conducted for 24 hours. At the end of the period, the emission was found to decrease by only 1%. The main qualities of this cathode are its high emission in pulsed conditions (30 amp/cm 2) and its low working temperature (950 to 1200°K). The shortcoming of this cathode is the need to activate it after exposure to the open air, which makes its use rather difficult. The pressed oxide-throium cathode is the strongest from the mechanical point of view. It is made of a sintered ceramic-metal mixture, pressed from

Card 2/3

ACC NRI AR7002220

thorium oxide with the addition of a refractory metal (molybdenum or tungsten). These cathodes are characterized by the absence of sparking, they are easily activated, show great resistance to deactivation by residual gases and ion bombardment, and have a very slow decay of emission during current takeoff. The capacity of the cathode to give a considerable emission in the pulse makes it possible for the cathode to work with pulses of long duration without a noticeable decay in the emission current, and also to work in large duty cycles. The influence of the degree of evacuation on the emission was tested. Readings were made of the emission characteristics at 8.10⁻⁵ mm Hg and 2.10⁻⁴ mm Hg. At 8.10⁻⁵ mm Hg, the emission qualities of the cathode did not change, and at 2.10⁻⁴ mm Hg, they changed insignificantly. The bibliography has 2 references. [Translation of abstract]

SUB CODE: 09/

Card 3/3

HOSKOV. D., delegat XXI s yesda Kommunisticheskoy partii Sovetskogo Soyuza, Geroy Sotsialisticheskogo Truda

This is where the savings are hidden. Sov.profesiuzy 7 no.4:10-11 Fe *59. (KIRA 12:5)

1. Master domernoy pechi Chusovskogo metallurgicheskogo zavoda. (Chusovoy--Metallurgy)